State of California AIR RESOURCES BOARD

EXECUTIVE ORDER D-277-3 Relating to Exemptions Under Section 27156 of the Vehicle Code

B & M RACING PERFORMANCE PRODUCTS 7 PSI. SUPERCHARGER KIT

Pursuant to the authority vested in the Air Resources Board by Section 27156 of the Vehicle Code; and

Pursuant to the authority vested in the undersigned by Section 39515 and Section 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the installation of the Supercharger Kit, manufactured and marketed by B & M Racing Performance Products, 9152 Independence Avenue, Chatsworth, California, 91311 has been found not to reduce the effectiveness of the applicable vehicle pollution control system and, therefore, is exempt from the prohibitions of Section 27156 of the Vehicle Code for the following General Motors applications as listed in Exhibit A, which is attached hereto and incorporated herein.

The Supercharger Kit includes the following main components: Roots type blower, intake manifold, fuel pressure regulator, new air cleaner lid and element, 160 degree thermostat, and new PROM chip on those with removable PROMs.

This Executive Order is valid provided that the installation instructions for the supercharger will not recommend tuning the vehicle to specifications different from those of the vehicle manufacturer.

Changes made to the design or operating conditions of the supercharger, as exempt by the Air Resources Board, which adversely affect the performance of the vehicle's pollution control system shall invalidate this Executive Order.

Marketing of the supercharger using any identification other than that shown in this Executive Order or marketing of the supercharger for an application other than those listed in this Executive Order shall be prohibited unless prior approval is obtained from the Air Resources Board. Exemption of the supercharger shall not be construed as exemption to sell, offer for sale, or advertise any component of the kit as an individual device.

This Executive Order does not constitute any opinion as to the effect the use of the supercharger may have on any warranty either expressed or implied by the vehicle manufacturer.

This Executive Order is granted based on comparative intake manifold air pressure that was recorded during a Hot-Start 505 LA4 drive cycle in the baseline and modified configuration. Test data showed that the B & M supercharger did not operate during the Hot-Start 505 drive cycle and thus could not affect the emissions of the vehicle. However, the ARB finds that reasonable grounds exist to believe that use of the B & M supercharger may adversely affect emissions of motor vehicles when operating under conditions outside the parameters of the previously prescribed test procedures. Accordingly, the ARB reserves the right to conduct additional emission tests, in the future, as such tests are developed, that will more adequately measure emissions from all cycle phases. If such test results demonstrate that the supercharger adversely affects emissions during off-cycle conditions (defined as those conditions which are beyond the parameters of the Cold-Start CVS-75 Federal Test Procedure), this Executive Order shall be effectively rescinded as of the date the test results are validated. Further, if such test results or other evidence provides the ARB with reason to suspect that the supercharger will affect the durability of the emission control systems, B & M shall be required to submit durability data to show that the durability of the vehicle emission control system is not, in fact, affected and/or that the add-on or modified part demonstrates adequate durability.

In addition to the foregoing, the ARB reserves the right in the future to review this Executive Order and the exemption provided herein to assure that the exempted add-on or modified part continues to meet the standards and procedures of Title 13, California Code of Regulations, Section 2222, et seq.

THIS EXECUTIVE ORDER DOES NOT CONSTITUTE A CERTIFICATION, ACCREDITATION, APPROVAL, OR ANY OTHER TYPE OF ENDORSEMENT BY THE AIR RESOURCES BOARD OF ANY CLAIMS OF THE APPLICANT CONCERNING ANTI-POLLUTION BENEFITS OR ANY ALLEGED BENEFITS OF B & M RACING PERFORMANCE PRODUCTS' SUPERCHARGER KIT.

No claim of any kind, such as "Approved by the Air Resources Board", may be made with respect to the action taken herein in any advertising or other oral or written communication.

Violation of any of the above conditions shall be grounds for revocation of this order. The order may be revoked only after a ten-day written notice of intention to revoke the order, in which period the holder of the order may request in writing a hearing to contest the proposed revocation. If a hearing is requested, it shall be held within ten days of receipt of the request and the order may not be revoked until a determination after hearing that grounds for revocation exist.

Executed at El Monte, California, this

.

day of October 1996.

R. B. Summerfield, Chief 'Mobile Source Operations Division

Valven putier	Cusuk british	DIOMOL DISD	NOIES IMBURI I	Model Year(a)	Displacement	Engine Group	ON has Mass
2.86"	"00.8	144 वर्ष	76.60	<u> 26-7891</u>	P49 143	119 110	155500
2.86"			309 7₹	2661 70-7081	bi8 - 17.8	Small Block	A2002Se
2.86"		ी दा द दांव	ISUNAM	1883	pi8 - 7 / 9		92201
7.86"		144 वंव	30614	1881	bis - 1 7.8		20228
2.86"			INJUEN	1994	DIS - 7 1'S		8550¢
2.86"			3097⊁	9661	P18 - 7 L'S		90228
2.86"			heuneM	1882	DIS - 7 L'S		90226
2,50"			3190	09-7891	OH - 7 L'S		A00528
2.50"			30977	1991-3	QH-72'9		92207
2,60"		 	leuneM	£-1991	OH - 17.8		92206
2.50"			41.60E	1661	QH-17.3		85208
2,50"			lauraM	1861	QH - 7 L'9		92210
2.50"			306JA	1882	OH - 7 4'S		92211
2,50"			ISUAM	1889	OH-77.9		92212
3.23"			41.60	28-7881	6.0 L - 8td		92200C
3.23"			30977	1863	5.0 L - Std		92213
3.23"			Mannial	1003	PIS - 70'9		32214
3.23"		ted cid	₹097	1884	5.0 L - Std		92215
3.23")BunaM	1881	P18 - 7 0'9		32216
3.23"			₹7.90E	1889	5.0 L - 9td		11226
3.23"		रेष्य दांव	Manual	9861	PIS - 7 0'S		81226
.987		144 dd	08 JE	06-7881	QH-70'S		35500C
.98.2	00.8	। १५६ व्यव	4L60E	1881-3	0H-10'S		81228
2,8 6 "	00'9	اجر عام	Manual	£-1681	3,0 L - HD		92220
.88.Z	00.8	र प्रव	4180E	1881	201-10		3221
.98.Z	,,00.8	144 वंद	IsunsM	1681	GH-10.8		7777
2.86"	00'8	144 व्यव	∃08J4	9881	2.0 L - HD		32223
3.23"			0878		P18 - 71-Z		00626
3.23"			BuneM		PIS - 71/2		10628
3.23"			ISUNEM	98-7891	PIS - 77'L		12302
3.23"				0661	P18 - 77 Z		EOEZ
3.23"							32304
3.23"				1991-93	17- Std		5305
3.23"							9052
3.23"			A		7.4L - Std	<u> </u>	70626
3.23"							80826
3.23"						 	60626
	EEL 2	174 ad	IBUNBM	1862	PIS - 71/2	•	2310

Page 1

B&M Part No.	Engine Group	Displacement	Model Year(s)	Transmission	Blower Disp	Crank pulley	Driven pulley
92401	90° V8 810-15	4.3 L - TBI	1988	4L60	112 cld	6.00"	2.86"
92402		4.3 L - TBI	1988	Manual	112 old	6.00"	2.86"
92403		4.3 L - TBI	1989	4L80	112 cld	6.00 ^H	2.88"
92404		4.3 L - TBI	1989	Manual	112 cid	6.00"	2.86"
92405		4.3 L - TBI	1990	4L60	112 dd	6.00"	2.86"
92406		4.3 L - TBI	1990	Manual	112 cid	6.00"	2.86"
92407		4.3 L - TBI	1991	4L80	112 cid	6.00°	2,86"
92408		4,3 L - TBI	1991	Manual	112 dd	6.00"	2.86"
92409		4.3 L - TBI	1992	4L60	112 cid	6,0 0"	2.88"
92410		4.3 L - TBI	1992	Manual	112 cld	6.00"	2.86"
92411		4.3 L - TBI	1983	4L60E	112 dd_	6.00°	2.86"
92412		4.3 L - TBI	1993	Manueri	112 old	6.00"	2.86"
92413		4.3 L - TBI	1994	4L60E	112 cla	6.00"	2.86"
92414		4.3 L - TBI	1994	Manual	112 cid	6.00"	2.86"
92415		4.3 L - TBI	1995	4L60E	112 cid	6.00"	2.56"
92416		4.3 L - TBI	1995	Manual	112 dd	6.00"	2.86"
92431	90° V6 CK	4.3 L - TBI	1988	4L60	112 cid	8,00"	2.88"
92432		4.3 L - TBI	1988	Manual	112 ¢id	G.00"	2.88"
92433		4.3 L - TBI	1989	4L60	112 cid	6.00"	2.86"
92434		4.3 L - TBI	1989	Manuel	112 cid	6.00"	2.86"
92435		4.3 L - TBI	1990	4L60	112 cld	6.00"	2.86"
92438		4.3 L - TBI	1990	Manual	112 dd	6.00"	2.86"
92437		4.3 L - TBI	1991	41.60	112 cid	6.00"	2.86"
92438		4.3 L - TBI	1991	Manual	112 ald	6.00"	2.86"
92439		4.3 L - TBI	1992	4L80	112 cld		2.86"
92440		4.3 L - TBI	1992	Manual	112 cid	6.00"	2.86"
92441		4.3 L - TBI					2.86"
92442		4.3 L - TBI	1993	Manuel	112 cld	6.00"	2,86"
92443		4.3 L - TBI	1994				2.86"
32444	_	4.3 L - TBI	1994	Manual			2.86"
2445		4.3 L - TBI	1995	4L60E			2.86"
22446		4.3 L - TBI	1995	Manual	112 cld		2,86"